

Safety Data Sheet



1. Identification of the Substance/Mixture and the Supplier

Supplier : National Institute of Advanced Industrial Science and Technology (AIST)
 Address : 1-3-1 Kasumigaseki, Chiyoda, Tokyo, Japan
 Office in Charge : Reference Materials Office, Center for Quality Management of Metrology, National Metrology Institute of Japan
 Person in Charge : Certified Reference Material Staff
 Telephone No. : +81-29-861-4059 Fax No. : +81-29-861-4009
 Emergency Contact : Same as above

Creation date : February 28, 2020

Revised on : -

Arrangement number : 8152002

Identity of Substance/Mixture : Certified reference material NMIJ CRM 8152-b
 Polyvinyl Chloride (for Phthalate Esters Analysis)
 Recommended Use of the Chemical and Restriction on Use : This reference material can be used for analysis instruments or measurement accuracy control and for the validation of measurement methods in the analysis of phthalate esters in PVC resins. This material shall not be used for purposes other than testing and research.

2. Hazards Identification

GHS classification : Acute toxicity (oral) : Classification 4
 Acute toxicity (dermal) : Classification 4

GHS-labeling element :



Signal word : Warning
 Hazard and toxicity information : Harmful if swallowed.
 Harmful in contact with skin.
 Cautionary statement : [Safety Measures]
 Do not handle until all the safety instructions are read and understood.
 Obtain the instructions manual prior to use.
 Do not use for purposes other than testing and research.
 Wash hands thoroughly after handling.
 Do not eat, drink, or smoke when using this product.
 Wear protective gloves, protective glasses, and protective shield.
 [Emergency Measures]
 Ingestion: Rinse mouth. If the person feels sick, contact a physician.
 Skin contact: Wash with plenty of water. If any abnormal state is

identified, seek medical attention.
 Take off the contaminated clothing and wash before reuse.
 [Storage]
 After filling argon gas to seal, keep out of light and store in a sealed condition in a clean area at 35 °C or lower.
 Do not turn upside down.
 [Disposal]
 Follow the related regulations and ordinances of the local government.
 Use a waste-treatment firm certified by prefectural governor.

Classification is impossible or not applicable for hazards not mentioned above.

3. Composition/Information on Ingredients

Substance or mixture : Mixture

Ingredient 1

Chemical name : Polyvinyl chloride
 Synonym : PVC
 Chemical formula : $(C_2H_3Cl)_x$
 Molecular weight : -
 CAS number : 9002-86-2
 Content : Approximately 79 %
 Reference Number in : Act on the Evaluation of Chemical Substances and Regulation of
 Gazetted List in Japan Their Manufacture, etc. : (6)-66
 Industrial Safety and Health Act : Published

Ingredient 2

Chemical name : Acetyl tributyl citrate
 Synonym : ATBC
 Chemical formula : $C_{20}OH_{34}O_8$
 Molecular weight : 402.48
 CAS number : 77-90-7
 Content : Approximately 12 %
 Reference Number in : Act on the Evaluation of Chemical Substances and Regulation of
 Gazetted List in Japan Their Manufacture, etc. : (2)-1327
 Industrial Safety and Health Act : Published

Other ingredients (additive) : 8 %

Content : The following materials are contained.
 Zinc stearate, calcium stearate composite (stabilizer): approximately 5.6 %,
 Epoxidized soybean oil (heat stabilizing auxiliary agent): approximately 1.6 %,
 Alkyl methacrylate, alkyl acrylate-styrene copolymer (processing auxiliary agent):
 approximately 0.8 %,

6. Accidental Release Measure

- Personal precautions : Promptly remove all potential ignition sources from peripheral areas. In case of ignition, prepare the equipment for firefighting.
- Protective equipment and emergency measures : When accidental release takes place indoors, thoroughly clear the air until the emergency measures are complete. Before the operation, wear appropriate protective equipment to protect skin from droplets and to prevent inhalation of dust and gas.
- Environmental precautions : Prevent the released product from being drained into a river or other area that might cause environmental damage. Prevent the polluted discharge from being drained into the environment without being processed properly.
- Recovery and neutralization : Collect the leaked product in an empty container. Then, wash and clean the spilled area with plenty of water.
- Prevention of secondary accidents : Surround the area with a rope, etc., to prevent unauthorized people from entering the area. Work from the windward side and evacuate people to the leeward side.

7. Handling and Storage

Handling

- Technical measures : Avoid contact with strong oxidants.
- Local ventilation and general ventilation : In case steam or mist is generated, seal the source and provide local exhaust ventilation.
- Precautions for safe handling : Avoid rough handling such as dropping, shocking, dragging, or otherwise agitating the container.
Seal the container after use.
Wash hands, face, and other necessary parts thoroughly, and gargle after handling.
Do not eat, drink, or smoke in places other than the designated areas.
Do not bring gloves and other contaminated protective equipment into the break area.
Only authorized people should be allowed in the handling area.
Wear appropriate protective equipment to prevent inhalation, or contact with eyes, skin, or clothing.
When handling indoors, provide local exhaust ventilation.

Storage

- Appropriate storage conditions : After filling argon gas to seal, keep out of light and store in a sealed condition in a clean area at 35 °C or lower.
Do not turn upside down.
- Safe packaging materials : Glass

8. Exposure Controls/Personal Protection

Standard control concentration

N/A

Threshold limit values (material name) Polyvinyl chloride

- ACGIH TLV-TWA : 1 mg/m³ respirable fraction
- Value recommended by Japanese Society of Occupational Health : N/A

Society of Occupational Health

- OSHA PEL TWA : N/A

Threshold limit values (material name) Acetyl tributyl citrate (ATBC)

- ACGIH TLV-TWA : N/A
- Value recommended by Japanese Society of Occupational Health : N/A

Society of Occupational Health

- OSHA PEL TWA : N/A

Engineering controls

Ventilation and emission : Local ventilation equipment or general ventilation equipment

Safety management and gas detection : Measuring device, detection tube

Storage precautions : Ventilate along the floor surface and seal the container. Keep away from combustible/reducing materials and strong oxidants.

Protective equipment

Respiratory protection : Dust mask

Hand protection : Protective gloves

Eye protection : Protective glasses with side wall (goggle type or full-face protective glasses as needed)

Skin and body protection : Protective clothing

Hygiene measures

Handle in accordance with the industrial hygiene and safety standards.

9. Physical and Chemical Properties

- Appearance, etc. : Pellet
- Color : Grayish white
- Odor : No data
- pH : No data
- Melting point : No data
- Boiling point : No data
- Flashing point : No data
- Explosive range : No data
- Vapor pressure : No data
- Relative vapor density(Air=1) : No data
- Specific gravity or bulk specific gravity : No data
- Solubility : Insoluble in water. Although it is insoluble in most

organic solvents, it is soluble in cyclohexanone, tetrahydrofuran, and nitrobenzene.

- *n*-Octanol/water partition coefficient (Log Po/w) : No data
- Auto-ignition temperature : No data

10. Stability and Reactivity

- Stability : Stable under normal conditions.
- Reactivity : Stable under normal conditions.
- Possibility of hazardous reaction : No data
- Conditions to avoid : Sunlight and high temperature
- Incompatible materials : No data
- Hazardous decomposition products : Carbon monoxide, carbon dioxide, halide

11. Toxicological Information

- Acute toxicity (oral) Polyvinyl chloride: LD₅₀ (rat) 2000 mg/kg or greater
Classified as Classification 4 according to LD₅₀ (rat) 22.5 ml/kg of the component contained in the additive (epoxidized soybean oil: approximately 1.6%).
- Acute toxicity (dermal) Classified as Classification 4 according to LD₅₀ (rabbit) 20 ml/kg of the component contained in the additive (epoxidized soybean oil: approximately 1.6%).

* As there is no information for the compound, the toxicological information is created based on the information on raw materials.

This product is stable under normal conditions and there is no risk of elution of hazardous additive components, etc.; however, use the product with sufficient safety measures in case it is handled under special conditions such as use with heat.

12. Ecological Information

- Ecotoxicity : No data
- Persistence and Degradability : No data
- Bioaccumulative Potential : No data
- Mobility in soil : No data
- Influence to the ozone layer : No data

13. Disposal Considerations

- Residues : Incinerate in an incinerator with exhaust gas processor (800 °C or over) or landfill as non-hazardous waste.
Follow the related regulations and ordinances of the local

government for disposal.
If it is impossible to dispose by the procedures described above,
use a waste-treatment vendor certified by prefectural governor.

Contaminated containers and packaging : To dispose of an empty container, completely remove the contents.

14. Transport Information

UN Dangerous : Not applicable
Goods Number
UN : -
classification
Product name : -
Packing Group : -
ICAO/IATA : Not applicable
Marine : Not applicable
Pollutant
Matters to be attended to : Avoid direct sunlight. Prevent leakage and fires caused by overturning, falling, etc. and transport with caution.

15. Regulatory Information

Industrial Safety and Health Law
 • Article 57-2 (Enforcement Order: Article 18-2) Hazardous substance whose name, etc. must be notified No.324, No.478, No.479
 ◇This SDS is originally prepared for the use of the material in Japan, thus the stated laws and regulations are stipulated and carried out in Japan. The use of the material in other countries should be referred to and by application of the relevant laws and regulations of the country in which the material will be used.

16. Other Information

Other
 The information in this document is not intended to be exhaustive and is based on currently available information and data. The measures given in this document are applicable only to normal handling conditions. When handling this reference material under special conditions etc., it is recommended to take safety measures appropriate to each specific application and context of use. This document is intended to provide information and not intended to guarantee anything in handling this reference material.